



## ***Open solution: The platform dispenser, open***

*Platform dispenser in stainless steel with one platform. Load capacity max. 300 kg. Safeguarded against tilting and tipping. Dispensing height can be adjusted using springs. Safety pushing handle. 4 corner bumpers. Rustproof castors in accordance with DIN 18867, Part 8. Wheel diameter 125 mm. 2 swivel castors, 2 swivel castors with brake.*

### ***Storage:***

*Three installed plate tubes  
(POK-Q1/1)*

### ***Impact protection:***

*Impact protection in plastic*

### ***All-in-one:***

*Tray shelf and  
cutlery top (option)*





Type	PO-SV1/1	PO-SV2/1	PO-GN2/1	PO-Q1/1	PO-TA1/1	POK-Q1/1 with 3 plate tubes
Length mm	730	1088	880	730	700	958
Width mm	690	690	690	690	500	690
Height mm	911	911	911	911	911	911
Platform dimensions mm	412 x 555	812 x 555	662 x 555	537 x 555	535 x 412	537 x 555
Basket/tray dimensions mm	max. 530 x 400	max. 530 x 800	max. 530 x 650	max. 500 x 500	max. 530 x 400	max. 500 x 500
Stack height approx. mm	575	575	575	575	575	575
Stack height						
Plate tubes approx. mm	–	–	–	–	–	520
Tube dimensions						
Plate tube clearance mm	–	–	–	–	–	170 x 170
Weight approx. kg	43	53	48	44	38	69
<b>Order no.</b>	<b>89 02 03 01</b>	<b>89 02 03 02</b>	<b>89 02 03 03</b>	<b>89 02 03 04</b>	<b>89 02 03 06</b>	<b>89 02 03 07</b>

**Storage capacity (No.) baskets in stainless steel/rilsan steel wire (optional)**

530 x 400 mm, 85 mm high	6	12	–	–	6	–
530 x 400 mm, 120 mm high	4	8	–	–	4	–
530 x 800 mm, 85 mm high	–	6	–	–	–	–
530 x 800 mm, 120 mm high	–	4	–	–	–	–
530 x 650 mm, 75 mm high	–	–	7	–	–	–
530 x 650 mm, 115 mm high	–	–	5	–	–	–
530 x 325 mm, 115 mm high CNS	–	–	10	–	–	–
500 x 500 mm, 75 mm high	–	–	–	7	–	7
500 x 500 mm, 115 mm high	–	–	–	5	–	5

**Storage capacity (No.) baskets plastic (optional)**

500 x 500 mm, 70 mm high	–	–	–	8	–	8
500 x 500 mm, 70 mm high	–	–	–	5	–	5
with crockery basket top, 41 mm high (Total height 106 mm)						

**Accessories**

Cutlery top with cutlery containers	<b>89 06 09 03</b>	<b>89 06 09 03</b>	<b>89 06 09 03</b>	<b>89 06 09 03</b>	–	–
--	--------------------	--------------------	--------------------	--------------------	---	---

**Tray holder on the side**

**for stacking trays**

for models PO-SV1/1, PO-TA1/1  
(details of dishwasher type required)

**All-round bumper**

**Antistatic tyres ø 125 mm**

**Galvanised castors ø 125 mm**



## **Closed solution:**

### **The platform dispenser closed, also refrigerated**

Platform dispenser closed, in stainless steel with one platform. Load capacity max. 300 kg. Safeguarded against tilting and tipping. Dispensing height can be adjusted using springs. Safety pushing handle. 4 corner bumpers. Rustproof castors in accordance with DIN 18867, Part 8. Wheel diameter 125 mm. 2 swivel castors, 2 swivel castors with brake.

**Version K = Circulating air-cooled with installed stainless steel lid:** Double-walled insulated carcass.

Lid 68 mm high, insulated with seal, can be folded up 90° and fixed into position. Switch elements are impact protected. Spiral cable 2.5 m, ON/OFF switch, blind socket. Cooling range approx. +5 °C to +8 °C (when lid is closed).

Refrigerant R 134a. Rated voltage 1N AC 230V 50 Hz.

Impact protection:  
Corner bumpers in plastic

Load-bearer:  
Platform with  
300 kg load capacity

Everything close at hand:  
Switch elements, spiral cable  
and safety pushing handle





PG-GN2/1



PK-Q1/1

Type	PG-GN2/1	PG-SV2/1	PG-Q1/1	PK-Q1/1	PG-4S	PG-6S
Length mm	880	1040	730	1164	790	1090
Width mm	690	690	690	814	690	690
Height mm	911	911	911	945	911	911
Platform dimensions mm	535 x 660	535 x 810	535 x 505	535 x 505	566 x 566	857 x 566
Basket / tray dimensions mm	max. 530 x 650	max. 530 x 800	max. 500 x 500	max. 500 x 500	–	–
Stack height approx. mm	600	600	600	600	600	600
El. connected load kW	–	–	–	0,410	–	–
Refrigeration output Watt at VT -10 °C	–	–	–	460	–	–
Weight approx. kg	68	65	62	140	57	65
<b>Order no.</b>	<b>89 02 02 01</b>	<b>89 02 02 06</b>	<b>89 02 02 02</b>	<b>89 02 04 01</b>	<b>89 02 02 03</b>	<b>89 02 02 04</b>

**Storage capacity (No.) baskets in stainless steel/rilsan steel wire (optional)**

530 x 400 mm, 85 mm high	–	14	–	–	–	–
530 x 400 mm, 120 mm high	–	10	–	–	–	–
530 x 800 mm, 85 mm high	–	7	–	–	–	–
530 x 800 mm, 120 mm high	–	5	–	–	–	–
530 x 650 mm, 75 mm high	8	–	–	–	–	–
530 x 650 mm, 115 mm high	5	–	–	–	–	–
500 x 500 mm, 75 mm high	–	–	8	8	–	–
500 x 500 mm, 115 mm high	–	–	5	5	–	–
500 x 500 mm, 70 mm high	–	–	8	8	–	–
500 x 500 mm, 70 mm high with crockery basket top, 41 mm high (Total height 106 mm)	–	–	5	5	–	–

**Accessories**

Insert tray with slit holes	<b>89 07 10 02</b>	<b>89 07 10 04</b>	<b>89 07 10 01</b>	<b>89 07 10 01</b>	–	–
Stainless steel lid, low	<b>89 07 02 01</b>	<b>89 07 14 01</b>	<b>89 07 01 01</b>	–	<b>89 07 03 01</b>	<b>89 07 04 01</b>
Stainless steel lid, high	<b>89 07 02 02</b>	<b>89 07 14 02</b>	<b>89 07 01 02</b>	–	<b>89 07 03 02</b>	<b>89 07 04 02</b>

**All-round bumper**

**Antistatic tyres ø 125 mm**

**Galvanised castors ø 125 mm**





## **Hot solution: The platform dispenser, circulating air-heated and the meal tray dispenser, circulating air-heated**

Platform dispenser, closed, in stainless steel with a square platform. Load capacity max. 300 kg. Safeguarded against tipping and tilting. Dispensing height adjustable using springs. Safety pushing handle. 4 corner bumpers. Rustproof castors in accordance with DIN 18867, Part 8. Wheel diameter 125 mm. 2 swivel castors, 2 swivel castors with brake. Double-walled insulated carcass. Switch elements are impact protected, spiral cable 2.5 m, ON/OFF switch, blind socket. Thermostat regulation from +30 °C to +110 °C. Circulating air heating. Rated voltage 1N AC 230V 50 Hz. VDE approved/GS approved/splash-water protected. **Dispenser is not suitable for plastic baskets!** Meal tray stacker version PU-M 2/1: Hinged lid in stainless steel, double-walled insulation, with safety handle, can be folded up. Dispenser is only suitable for stainless steel baskets (without coating)!

Quality symbol:  
Tip and tilt-proof  
platform

Everything close at hand:  
Switch elements, spiral cable  
and pushing handle

Impact protection:  
Corner bumpers in plastic





PU-GN 2/1 / PU-GN/SV 1/1



PU-GN2 1



PU-M 2/1

Type	PU-GN 2/1	PU-SV 2/1	PU-Q 1/1	PU-GN/SV 1/1	PU-M 2/1
Length mm	990	1142	840	740	1148
Width mm	690	690	690	690	744
Height mm	911	911	911	911	911
Platform dimensions mm	535 x 660	535 x 810	535 x 510	535 x 410	535 x 660
Basket/tray dimensions mm max.	max. 530 x 650	max. 530 x 800	max. 500 x 500	max. 530 x 400	max. 530 x 650
Stack height approx. mm	600	600	600	600	600
El. connected load kW	2.240	2.240	2.240	2.240	2.250
Weight approx. kg	85	92	72	71	109
<b>Order no.</b>	<b>89020103</b>	<b>89020102</b>	<b>89020104</b>	<b>89020101</b>	<b>89020107</b>

#### Storage capacity baskets (No.)

##### in stainless steel/rilsan steel wire (optional)

530 x 400 mm, 85 mm high	–	14	–	7	–
530 x 400 mm, 120 mm high	–	10	–	5	–
530 x 800 mm, 85 mm high	–	7	–	–	–
530 x 800 mm, 120 mm high	–	5	–	–	–
530 x 650 mm, 75 mm high	8	–	–	–	8
530 x 650 mm, 115 mm high	5	–	–	–	–
500 x 500 mm, 75 mm high	–	–	8	–	–
500 x 500 mm, 115 mm high	–	–	5	–	–

#### Accessories

<b>Insert tray with slit perforations</b>	<b>89071002</b>	<b>89071004</b>	<b>89071001</b>	<b>89071003</b>	–
---	-----------------	-----------------	-----------------	-----------------	---

<b>Stainless steel lid high</b>	<b>89070601</b>	<b>89070801</b>	<b>89070501</b>	<b>89070701</b>	–
---------------------------------	-----------------	-----------------	-----------------	-----------------	---

#### All-round bumper

#### Antistatic tyres ø 125 mm

#### Galvanised castors ø 125 mm

not for PU-M 2/1

#### Important!

Plastic baskets are not suitable for heated crockery dispensers.